

Wave Springs



Wave springs are typically used in conjunction with vee packing sets to apply a constant load to the seals. They are also found in some telescopic cylinders. Please consult sales for sizes not listed.

Part Number	Operates in Bore	Clears Shaft	Work Height	Free Height	Thickness	Radial Wall	Vee Packing		Price
							Rod	Gland	
SSR-0112	1.12	0.84	0.078	0.13	0.016	0.133	5/8	1-1/8	\$ 3.78
SSR-0150	1.50	1.17	0.078	0.17	0.018	0.143	1	1-1/2	\$ 3.78
SSR-0162	1.62	1.31	0.078	0.20	0.018	0.143	1-1/8	1-5/8	\$ 3.78
SSR-0175	1.75	1.44	0.078	0.14	0.018	0.143	1-1/4	1-3/4	\$ 3.78
SSR-0187	1.87	1.56	0.078	0.15	0.018	0.143	1-1/4	1-7/8	\$ 3.78
SSR-0200	2.00	1.68	0.093	0.14	0.024	0.150	1-3/8	2	\$ 3.78
SSR-0212	2.12	1.80	0.093	0.15	0.024	0.150	1-1/2	2-1/8	\$ 17.38
SSR-0225	2.25	1.93	0.093	0.17	0.024	0.150	1-5/8	2-1/4	\$ 3.89
SSR-0250	2.50	2.12	0.093	0.17	0.024	0.178	1-7/8	2-1/2	\$ 3.97
SSR-0262	2.62	2.24	0.093	0.19	0.024	0.178	2	2-5/8	\$ 4.01
SSR-0275	2.75	2.34	0.109	0.17	0.030	0.188	2-1/8	2-3/4	\$ 4.25
SSR-0300	3.00	2.59	0.109	0.19	0.030	0.188	2-3/8	3	\$ 4.92
SSR-0325	3.25	2.75	0.109	0.20	0.030	0.233	2-1/2	3-1/4	\$ 5.03
SSR-0350	3.50	3.00	0.109	0.23	0.030	0.233	2-3/4	3-1/2	POR
SSR-0375	3.75	3.25	0.109	0.26	0.030	0.233	3	3-3/4	\$ 6.78
SSR-0400	4.00	3.50	0.109	0.19	0.030	0.233	3-1/4	4	\$ 15.83
SSR-0425	4.25	3.74	0.109	0.21	0.030	0.233	3-1/2	4-1/4	\$ 17.78
SSR-0625	6.25	5.73	0.125	0.34	0.030	0.233	5-3/8	6-1/4	\$ 71.95
SSR-0900	9.00	8.18	0.156	0.29	0.032	0.375	8	9	\$ 78.09
SSR-0950	9.50	8.68	0.156	0.24	0.032	0.375	8-1/2	9-1/2	\$ 141.28

Ret. Rings / Wave Springs