

U Type Universal Urethane Wipers - Inch, cont'd.

Part Number	Wiper Dimensions				Groove Dimensions		
	Rod Dia. d	O.D. D ₁	Base Ht L ₁	Total Seal Ht L ₂	+0.006 -0.000 D	+0.004 -0.000 L	+0.010 -0.000 F
959-61SA1889	8.000	8.500	0.250	0.375	8.500	0.250	
U-8000	8.000	8.750	0.374	0.585	8.747	0.375	8.493
U-8250	8.250	9.000	0.374	0.585	8.997	0.375	8.743
959-62SA	8.500	9.000	0.250	0.375	8.997	0.250	
U-8500	8.500	9.250	0.374	0.585	9.247	0.375	8.993
U-8750	8.750	9.500	0.374	0.585	9.497	0.375	9.243
U-8875	8.875	9.625	0.374	0.585	9.622	0.375	9.368
U-9000	9.000	9.750	0.374	0.585	9.747	0.375	9.493
U-9000-500	9.000	10.000	0.499	0.775	10.000	0.500	9.659
U-9250	9.250	10.000	0.374	0.585	9.997	0.375	9.743
U-9500	9.500	10.250	0.374	0.585	10.247	0.375	9.993
U-9500-500	9.500	10.500	0.499	0.775	10.497	0.500	10.159
U-9750	9.750	10.500	0.374	0.585	10.497	0.375	10.243
U-10000	10.000	11.000	0.499	0.775	10.997	0.500	10.659
U-10250	10.250	11.250	0.499	0.775	11.247	0.500	10.909
U-10500	10.500	11.500	0.499	0.775	11.497	0.500	11.159
U-10625	10.625	11.625	0.499	0.775	11.622	0.500	11.284
U-10750	10.750	11.750	0.499	0.775	11.747	0.500	11.409
U-11000	11.000	12.000	0.499	0.775	11.997	0.500	11.659
U-11250	11.250	12.250	0.499	0.775	12.247	0.500	11.909
U-11500	11.500	12.500	0.499	0.775	12.497	0.500	12.159
U-12000	12.000	13.000	0.499	0.775	12.997	0.500	12.659
U-12500	12.500	13.500	0.499	0.775	13.497	0.500	13.159
U-13500	13.500	14.500	0.499	0.775	14.497	0.500	14.159
U-13750	13.750	14.750	0.499	0.775	14.747	0.500	14.409
U-14000	14.000	15.000	0.499	0.775	14.997	5.000	14.659
U-15000	15.000	16.000	0.499	0.775	15.997	0.500	15.659
U-16000	16.000	17.000	0.499	0.775	16.997	0.500	16.659
U-18000	18.000	19.000	0.499	0.775	18.997	0.500	18.659
U-20000	20.000	21.000	0.499	0.775	20.997	0.500	20.659
U-30000	30.000	31.000	0.499	0.775	30.997	0.500	30.659

U Wiper Nitrile Cord

ALTERNATIVE SEALS:
U-Wiper, 842, U-R, S34

EXAMPLE: 187UCORD N70

Cross Section	Style	Suffix
187	UCORD	N70
3/16"	UNIVERSAL WIPER CORD	70D NBR

This 70 durometer nitrile extrusion is available for those non-standard rod applications and some telescopic cylinders and will interchange into a standard U-wiper groove.

Temperature: -40° to 250°F

Part Number	Cross Section/Base Height
187UCORD N70	0.187

K Wiper Nitrile Cord

ALTERNATIVE SEALS:
K-Wiper, 7580

EXAMPLE: 187KCORD N70

Cross Section	Style	Suffix
187	KCORD	N70
3/16"	K WIPER CORD	70D NBR

This 70 durometer nitrile extrusion is available in two cross sections for those non-standard rod applications and will interchange into standard K and 7580 wiper grooves.

Temperature: -40° to 250°F

Part Number	Cross Section
187KCORD N70	0.187
250KCORD N70	0.250